

IN THE CLAIMS:

Please amend 1, 10, 13, 15 and 18 claims as follows:

1. (Currently Amended): A single-layer or multi-layer, heat-shrinkable film having comprising:

a layer of a thermoplastic resin material comprising an alicyclic structure-containing polymer (A), said polymer (A) comprising:

Chen
having a repeating unit (a) consisting of an alicyclic structure units, wherein a proportion of a repeating unit (b) of a ring structure having said alicyclic units have no norbornane ring structure in the repeating unit (a), said proportion is at least 10% by weight in said alicyclic units.

2. (Original): The heat-shrinkable film according to Claim 1, wherein the thermoplastic resin material layer is a layer of a resin composition comprising a soft polymer (B) in addition to the alicyclic-structure containing polymer (A).

3. (Original): The heat-shrinkable film according to Claim 1, which is a multi-layer, heat-shrinkable film further having at least one crystalline resin layer in addition to at least one layer of the thermoplastic resin material.

4. (Original): The heat-shrinkable film according to Claim 1, which is a film stretched at a draw ratio of at least 1.5 times in at least an uniaxial direction.

5. (Original): The heat-shrinkable film according to Claim 4, which is a film biaxially stretched at a draw ratio of 1.5 to 10 times in each of machine and transversal directions.

6. (Original): The heat-shrinkable film according to Claim 1, wherein the film impact retention after heat shrinking is at least 70%, and the rate of increase of water vapor transmission rate after heat shrinking is most 1.20.

7. (Original): The heat-shrinkable film according to Claim 1, wherein the heat shrinkage factor when the film is held under a temperature atmosphere ranging from a temperature lower by 40°C than the glass transition temperature of the alicyclic structure-containing polymer (A) to a temperature higher by 80°C than the glass transition temperature [(Tg - 40°C) to (Tg + 80°C)] is 3 to 70%.

8. (Original): The heat-shrinkable film according to Claim 1, which has a thickness of 1 to 100 μ m.

9. (Original): The heat-shrinkable film according to Claim 1, wherein the alicyclic structure-containing polymer (A) has a weight average molecule weight of 5,000 to 500,000, a glass transition temperature of 50 to 300°C and a melt flow rate of 0.5 to 150 g/10 min as measured at a temperature of 280°C under a load of 2.16 kg in accordance with JIS K 6719.

10. (Currently Amended): The heat-shrinkable film according to Claim 1, wherein a the proportion of the repeating unit (a) consisting of the polymer (A) made up by the alicyclic structure in the alicyclic struture-containing polymer (A) units is at least 50% by weight.

11. (Original): The heat-shrinkable film according to Claim 1, wherein the alicyclic structure-containing polymer (A) is a thermoplastic norbornene resin.

12. (Original): The heat-shrinkable film according to Claim 11, wherein the thermoplastic norbornene resin is a hydrogenated product of a ring-opening (co)polymer of a norbornene monomer.

13. (Currently Amended): The heat-shrinkable film according to Claim 11, wherein the repeating unit (b) of the ring structure the alicyclic units having no norbornane ring structure is a repeating unit are derived from a ring-opening (co)polymer of at least one norbonene monomer selected from the group consisting of norbornenes, dicyclopentadienes, methanotetrahydrofluorenes and methanohexahydroanthracenes.

14. (Original): The heat-shrinkable film according to Claim 12, wherein the alicyclic structure-containing polymer (A) is a hydrogenated product of a ring-opening polymer of a dicyclopentadiene.

15. (Currently Amended): The heat-shrinkable film according to Claim 12, wherein the alicyclic structure-containing polymer (A) is a hydrogenated product of a ring-opening copolymer of a norbornene and a dicyclopentadiene.

ab/Smiley
16. (Original): The heat-shrinkable film according to Claim 12, wherein the alicyclic structure-containing polymer (A) is a hydrogenated product of a ring-opening copolymer of a norbornene and a tetracyclododecene.

17. (Original): The heat-shrinkable film according to Claim 2, wherein the soft polymer (B) is a polymer having a glass transition temperature of at most 30°C.

18. (Currently Amended): The heat-shrinkable film according to Claim 3, wherein the crystalline resin is at least one polyolefin resin selected from the group consisting of polyethylene resins and polypropylene ~~reins~~ resins.

19. (Original): The heat-shrinkable film according to Claim 1, wherein the heat-shrinkable film is multi-layer, heat-shrinkable film, and a proportion of the thickness of the layer of the thermoplastic resin material comprising the alicyclic structure-containing polymer (A) is 10 to 90% based on the total thickness of the film.

Amendment under 37 C.F.R. §1.111
Issei ISHIMARU et al.

U.S. Patent Application Serial No. 09/831,378
Attorney Docket No. 010649

Issei Ishimaru
20. (Original): A package obtained by thermally shrink-wrapping a product to be packaged
with the heat-shrinkable film according to any one of the Claims set forth above.
